COMMERCIAL OPERATORS

IACKSHAFTS







PROUDLY ASSEMBLED IN NORTH AMERICA

- 1/2HP-115V-1PH Motor
- 3 Button station (NEMA 1)
- 1500 RPM, high starting torque motor with overload protection
- Inherent Mechanical Brake (I.M.B)
- LX 900 BOARD Standard Features (See Accessories cut sheet for more details)
 - B2 Mode, C2 Mode, TTC Mode
- On board, Open, Close, & Stop for ease of setting limits
- **■** Photo-eyes included
- Pre-wired to accept sensing devices
- 24 Volt accessory power
- On board (372 MHz) receiver capable of programming up to 20 transmitters
- **■** External receiver connection
- Ground level disconnect for manual operation
- NEMA 1 Electrical enclosure
- Adjustable friction clutch
- Maximum output shaft revolutions 22.5
- Primary Drive: Heavy Duty 4L V-Belt
- Secondary: #41 CHAIN / SPROCKETS
- Output: #41 CHAIN / SPROCKETS
- 27 RPM output shaft speed
- Door speed determined by the door system installed
- Standard sprockets:
 - Sectional: 41B14 x 1" bore to 41B18 x 1" bore
 - Steel Rolling: 41B14 x 1" bore to 41B24 x 1 1/4" bore
- Warranty
 - 2 years on parts and motor

MODEL	WASHDOWN MOD.	HOIST	#41 CHAIN	SOLENOID BRAKE	HP	V	PH	HEIGHT	LIST
MDJ-211					1/2	115	1	UP TO 20'	\$868.15
MD)-211	-	-	-	-	1/2	115	1	UP 10 20	фо00.13
MDJB-211	-	-	-	Y	1/2	115	1	UP TO 20'	\$953.44
MDJH-211	-	Y	-	-	1/2	115	1	UP TO 20'	\$942.25
WID)II-211	<u>-</u>	1	_	_	1/2	113	1	01 10 20	Ψ/12.23
MDJBH-211	-	Y	-	Y	1/2	115	1	UP TO 20'	\$1,027.53